






JP 2000


INTERCOOLER® | AC-DIRECT®
HIGH PERFORMANCE COOLING SYSTEM | ALTERNATIVE CURRENT DIRECT DRIVER

**DRIVERLESS®
REGULATION**

Model No	Input Voltage	Power	Angle	Color/Kelvin	Luminous Flux (LED)	IP Rating	Dimensions (mm)	Cos φ	Weight/Kg
JP-2000	220/240 VAC	60W	120°	3000-5000-6500	8000 Lumens	66	W180.0 X L200.0 X H60.0	>0,98	3,50
JP-2000-P	12~48 VDC	60W	120°	3000-5000-6500	8000 Lumens	66	W180.0 X L200.0 X H60.0	-	3,50



LIGHT DISTRIBUTION CURVE (LED)



LED AYDINLATMA / LED LIGHTING

- | İç ve Dış Aydınlatmalar
- | Indoor & Outdoor Lightings
- | Ofisler
- | Offices
- | Hotel & Restaurant
- | Garaj, Asansörler ve Otoparklar
- | Garages, Elevators and Parks
- | Mimari Aydınlatmalar
- | Architectural Lightings
- | Bahçe Aydınlatmaları
- | Garden Lightings

MADE IN TURKEY
johnsonled.com.tr